# **Vibrating Wire Weir Monitor**

### **Applications**

The Model 4675LV is used for the precision water level measurement and monitoring of...

- Weirs
- Tanks
- Stream levels
- Reservoir levels



• The Model 4675LV with cutaway revealing its internal components: a cylindrical weight suspended from the vibrating wire force transducer.

# **Operating principle**

The Model 4675LV is a precision water level monitoring system that uses a vibrating wire force transducer to provide a highly stable and sensitive means of monitor-ing water levels.

The main component is a cylindrical weight suspended from the vibrating wire force transducer. The cylinder hangs partially in the water whose level is to be monitored. As the water level changes, the changing buoyancy force on the cylinder acts directly on the vibrating wire transducer altering its tension and hence its resonant frequency.

In operation the vessel containing the Weir Monitor is connected hydraulically to the water whose level is to be measured. The vessel is positioned so that the bottom of the hanging cylinder is slightly below the bottom of the V-notch or flume.

# **Advantages and Limitations**

The main advantage of the 4675LV system lies in it's high sensitivity and stability, which allows water level changes of as little as 0.1 mm to be measured accurately.

The force transducer is immune to zero drift and has a very low response to temperature changes.

As with all vibrating wire sensors, because the output is a frequency, it is not affected by changes of cable resistance and hence long signal cables are not a problem.

The frequency is measured by either a portable readout or datalogger.

40-20 mA or 0-5 V outputs can be obtained using the Model 8020-59 VW Frequency to Analog Converter.





• Typical Model 4675LV installation.



• Nominal lengths and diameters of the Model 4675LV standard ranges.

### **System Components**

The cylinder and force transducer are contained within a housing made from slotted PVC pipe. This pipe can be positioned within the weir or tank or it can be installed in a Stilling Well connected hydraulically to the tank or weir. The vibrating wire transducer is vented to the atmosphere so that barometric fluctuations are compensated for automatically. The vent line terminates in a moisture trap which requires periodic maintenance to replace the desiccant.

#### **Technical Specifications**

Standard Ranges <sup>1</sup>	150, 300, 600, 1500 mm
Resolution	0.025% F.S. (minimum)
Accuracy <sup>2</sup>	±0.1% F.S.
Linearity	0.25% to 0.75%F.S.
Stability	±0.05% F.S. per year
Temperature Range <sup>3</sup>	-20°C to +80°C
Dimensions (L $\times ø$ )	165 × 25 mm (transducer)

<sup>1</sup>Other ranges available on request.

<sup>2</sup>Accuracy established under laboratory conditions. <sup>3</sup>Using anti-freeze solution can extend the range below 0°C.



GEOKON, INCORPORATED 48 Spencer Street Lebanon, NH 03766 · USA

phone: 1 · 603 · 448 · 1562 email: info@geokon.com web: www.geokon.com

GEOKON is an ISO 9001:2008 registered company

The GEOKON® logo and word mark are registered trademarks with the United States Patent and Trademark Office. GEOKON® maintains an ongoing policy of design review and reserves the right to amend products and specifications without notice